

Part Number: **F1WM2SCIVO**

Issue No 1—July 2018

Description: **FTTP customer wall mount 2 fibre outlet****Use / Application:**

This FTTP wall outlet, will achieve a long service life. The outlet houses two SC connector bulkheads for either single or two fibre services. A spring loaded flap covers the connector end position when not in use protecting from dust ingress or laser light output when connector not inserted. The unit has a full height, clip on ivory colored cover. The outlet mounts on a standard 84mm centers style flush box or mounting block.

**Features & Benefits:**

- Has a spring loaded flap that covers connector position, when not in use. This excludes dust and is a safety measure against viewing lasers
- Mounts on standard GPO flush boxes or mounting blocks at 84mm centers
- Supplied with shuttered SC through adaptors with a ceramic zirconia ferrule, < 0.1 dB insertion loss
- Manages 900 micron fibre or 2mm dia. cords internally, at an MBR of 15mm
- Manages 2.4mm, 2.9mm and 4.8mm nominal dia. premise cables, using 3 inputs
- Manages a fusion splice or a mechanical splice between the premise cable (either 2.4, 2.9 or 4.8mm dia.

**Technical Attributes:**

<b>Dimensions</b>	73mm (W) x 115mm (H) x 18mm (D)
<b>Weight</b>	60 g (Cover alone = 22 g)
<b>Materials</b>	Plastic
<b>Colour</b>	Ivory