



















HORNET LED FLOODLIGHT


More flexibility & less obtrusive than other floodlights on the market. Engineered to deliver absolute focus, optimum performance and robustness.

FEATURES:

- 3 year warranty
- Rated life 30,000h (20W) 50,000h (40W)
- Integrated LED driver
- Slim and compact design
- Adjustable head (300° horizontal and 200° vertical)
- Die-cast aluminium body
- Acrylic lens
- Complete with 1m cable
- Retro-fit accessory included for easy installation onto existing floodlight mounting points
- 120° beam angle (20W) 110° beam angle (40W)
- CCT 4000K, CRI>80
- IP66

APPLICATIONS:


- Residential
- Outdoor entertaining areas
- BBQ areas
- Access areas



VERSION	L (mm)	W (mm)	H (mm)	W1 (mm)
20W	125	125	23	186
40W	190	159	30	219



Adjustable head with 300° horizontal and 200° vertical flexible rotation.



HORNET LED FLOODLIGHT 20W 4000K

CODE	VERSION	WATTAGE	ССТ	CRI	DELIVERED LUMENS*	MASS
CFL20840	20W 4000K NON-DIM	20W	4000K	>80	1503lm	0.4kg
CFL40840	40W 4000K NON-DIM	40W	4000K	>80	3511lm	1.0kg

^{*}Delivered lumens from luminaire, including thermal, electrical and optic losses.



