

Watt	Lumens	Dimmable	CRI	Cut-Out	Overall
9W	710lm	Yes	85-90	76-86mm	100mm

Classification	Input	Colour Temp.	Life	Recess	Material
IC-F	230V Driver	3,000K	40,000hr	50mm	Aluminium

IP	Beam Angle	Warranty	Colour		Black
IP44	60 deg	5yrs	Matt White	Brush Chrome	Silver

PFC	Tilt Angle
0.90	30 deg

DLEK372 9W DIMMABLE ADJUSTABLE LED DOWNLIGHT

High quality COB LED dimmable downlight suitable for residential and commercial applications and suitable for replacement of 50 Watt dichroic downlights.

Suitable for highlighting wall, picture and art works with its versatile 30 deg centre tilting angle and narrow 60 deg beam

High lumen output and low running costs, minimal heat and long service life.

This downlight is IC-F complainant and Energy Star rated

Supplied with Samsung 85+ CRI LED Chips

Quality has not been compromised

KEY FEATURES

- High Lumen output 710 Lumens
- 3,000K colour temperature Warm White
- Easy installation and wiring with quick snap terminal cover
- 60 deg beam angle and 30 deg centre tilt adjustment
- Long Life 40,000hr
- Dimmable with Leading and trailing edge dimmers
- Low running costs only 9W with PFC 0.90
- Large terminals suitable for looping applications
- 130mm flange available DLA372
- Driver and Luminaire IC Rated and may be covered by approved fixed ceiling Insulation



SKU CODE	TRIM	LED COLOUR
DLEK372W	MATT WHITE	3,000K
DLEK372BC	BRUSHED CH	3,000K
DLEK372S	SILVER	3,000K

Note:
RED only driver Complies with Annex ZA of AS/NZS 60598.2.2:2001 Luminaires
Part 2.2: Particular requirements ☐ Recessed
luminaires incorporating New Zealand ☐ only
Amendment A.

