

STREAMLINE LED WIDE BODY BATTEN

PRODUCT DETAILS:




- Size: 4ft/1200mm, 5ft/1500mm
- Rated life: L70/B50 50000hrs
- LED: CCT 4000K, CRI>80
- Beam angle: 120°
- Driver (Eco): Integral, Non-Dim
- Driver (Pro): TCI, Integral, Non-Dim, DALI/PUSH/1-10V Dimming, Flicker-Free
- Rating: IP20, Class I
- Operating temperature: 0°C to +40°C
- Housing: Cold rolled steel, 170mm wide
- Finishing: White
- Diffuser: Polycarbonate, Frosted, Reeded
- Connection: 20mm knockout for conduit or cable glands from end or rear, Center cable entry, End to end mounting
- Warranty: 5 year

MADE TO ORDER OPTIONS:

6500K, Emergency

APPLICATIONS:

Surface mount, Internal
Schools, Libraries, Retail stores, Hospitals, Office areas



5FT/1500MM 61W 4000K

VERSION	L (MM)	W (MM)	H (MM)
4FT/1200MM	1166	170	79
5FT/1500MM	1466	170	79

CODE	DESCRIPTION	POWER [~]	LUMENS ⁺	EFFICACY	WEIGHT
STMLED4/4	ECO 4FT/1200MM 4000K CRI>80 NON-DIM	42W	4545lm	108lm/W	2.2kg
STMLEDPRO4/4	PRO 4FT/1200MM 4000K CRI>80 NON-DIM	42W	4545lm	108lm/W	2.2kg
STMLEDPRO4/4D	PRO 4FT/1200MM 4000K CRI>80 DALI	42W	4545lm	108lm/W	2.2kg
STMLED5/4	ECO 5FT/1500MM 4000K CRI>80 NON-DIM	61W	6730lm	110lm/W	2.7kg
STMLEDPRO5/4	PRO 5FT/1500MM 4000K CRI>80 NON-DIM	61W	6730lm	110lm/W	2.7kg
STMLEDPRO5/4D	PRO 5FT/1500MM 4000K CRI>80 DALI	61W	6730lm	110lm/W	2.7kg

*Delivered lumens from luminaire, including thermal, electrical and optic losses. [~]Tested system powers from luminaire.