



### Main

Range of product	500 Series
Product or component type	Switch
Quantity per set	Set of 10
Type of packing	Carton
Colour tint	White
Motor M-rating AS3133	M50

### Complementary

Control type	Rocker
Material	PC (polycarbonate)
Installation direction	Vertical
Surface finish	Gloss
Width	66 mm
Height	66 mm
Diameter	66 mm
Rated current	16 A/16 AX
[Ue] rated operational voltage	250 V AC 50 Hz
Network number of phases	1 phase
Number of gangs	1 gang
Number of poles	1
Connections - terminals	3 screw terminal
Clamping connection capacity	4 x 1.5 mm <sup>2</sup> 2 x 1.5 mm <sup>2</sup>
Device mounting	Ceiling
Fixing center	50 mm

### Environment

Ambient air temperature for operation	-10...40 °C
---------------------------------------	-------------

Disclaimer: This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications

**Packing Units**

---

Unit Type of Package 1	PCE
------------------------	-----

---

**Offer Sustainability**

---

EU RoHS Directive	Under investigation
Toxic heavy metal free	Yes
Mercury free	Yes
RoHS exemption information	<a href="#">Yes</a>
China RoHS Regulation	<a href="#">China RoHS declaration</a> Pro-active China RoHS declaration (out of China RoHS legal scope)

---