



Main

| | |
|---------------------------|---------------|
| Range of product | 56 Series™ |
| Range | 56 Series |
| Product brand | Clipsal |
| Product or component type | Rotary switch |
| Device application | Control |
| Colour tint | Grey |
| Motor M-rating AS3133 | M250 |
| Quantity per set | Set of 4 |
| Type of packing | Carton |

Complementary

| | |
|--------------------------------|--------------------|
| Number of poles | 3 |
| Control type | Rotary |
| Material | PC (polycarbonate) |
| Surface finish | Gloss |
| Installation direction | Vertical |
| Width | 95 mm |
| Height | 95 mm |
| Depth | 48 mm |
| Rated current | 50 A |
| [Ue] rated operational voltage | 415 V |
| [Ui] rated insulation voltage | 660 V |
| Network frequency | 50 Hz |
| Network number of phases | 3 phases |
| Number of gangs | 1 gang |
| Mounting mode | Surface mounted |
| Fixing center | 84 x 84 mm |

Disclaimer: This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications

| | |
|---------------------|------------------------|
| Cable cross section | 6...35 mm ² |
|---------------------|------------------------|

Environment

| | |
|---------------------------------------|-------------|
| IP degree of protection | IP66 |
| Ambient air temperature for operation | -40...55 °C |

Packing Units

| | |
|------------------|-----------|
| Package 1 Weight | 0.333 kg |
| Package 1 Height | 80.000 mm |
| Package 1 width | 95.000 mm |
| Package 1 Length | 95.000 mm |

Offer Sustainability

| | |
|----------------------------|---|
| Sustainable offer status | Green Premium product |
| EU RoHS Directive | Compliant EU RoHS Declaration |
| Mercury free | Yes |
| RoHS exemption information | Yes |
| China RoHS Regulation | China RoHS declaration Product out of China RoHS scope. Substance declaration for your information |
| Environmental Disclosure | Product Environmental Profile |