

■ WALL MOUNTING STRAIGHT BOX SOCKETS **SERIES 690**

MAIN TECHNICAL FEATURES:

- 20° Inclined industrial sockets according to the Standard EN 60309.
- Wall mounting straight box, ready for conduit Ø 20 or 25 mm.
- In currents of 16 and 32 A.
- Resistance to chemical or atmospheric agents.
- Stainless steel springs for lid closing.
- Dimensions 96x96x70 (WxHxD) mm.

CE

IP67

■ Wall mounting straight box sockets - EN 60309 - In 16A - IP67

ITEM	COLOUR	POLES	NOMINAL VOLTAGE	REFERENCE h	PACKAGING PIECES
EC694021D*		2P	20-25V~	without reference	12
EC694031D*		3P	20-25V~	without reference	12
EC691041D		2P+⊕	100-130 V~	4	12
EC691051D		3P+⊕	100-130 V~	4	12
EC690511D		2P+⊕	200-250 V~	6	12
EC692541D		3P+⊕	200-250 V~	9	12
EC690531D		3P+⊕	380-415 V~	6	12
EC690551D		3P+N+⊕	346-415 V~	6	12

■ Wall mounting straight box sockets - EN 60309 - In 32A - IP67

ITEM	COLOUR	POLES	NOMINAL VOLTAGE	REFERENCE h	PACKAGING PIECES
EC691061D		2P+⊕	100-130 V~	4	12
EC691071D		3P+⊕	100-130 V~	4	12
EC692561D		2P+⊕	200-250 V~	6	12
EC692571D		3P+⊕	200-250 V~	9	12
EC690571D		3P+⊕	380-415 V~	6	12
EC690591D		3P+N+⊕	346-415 V~	6	12

* item available on request



EC691041D



EC690511D



EC690531D