

2 Core, Figure 8 Parallel Webbed, V90 Clear PVC Insulation, OFHC Speaker Cable

EXTRA LOW VOLTAGE – NOT FOR MAIN CONNECTION



CONSTRUCTION	0.75mm ²	2.00mm ²
PRODUCT CODE	100m = AU-FSC224020 100M 500m = AU-FSC224020 500M	100m = AU-FSC264020 100M 500m = AU-FSC264020 500M
CONDUCTOR	Stranded Oxygen Free Plain Copper wire to AS/NZS 1125 Ø = 24*020±0.003 mm ²	Stranded Oxygen Free Plain Copper wire to AS/NZS 1125 Ø = 64*020±0.003 mm ²
VOLTAGE RATING	AC 50V / DC 120V to AS/NZS 3000:2000	AC 50V / DC 120V to AS/NZS 3000:2000
MAX DC RESISTANCE @ 20°C	25.23 Ω/mt	9.46 Ω/mt
INSULATION	V90 PVC to AS/NZS 3808:2000, UV Stabilised Colour: Clear with Red Stripe Thickness: 0.6±0.05mm	V90 PVC to AS/NZS 3808:2000, UV Stabilised Colour: Clear with Red Stripe Thickness: 0.7±0.05mm
NOMINAL O.D (mm)	2.45 x 5.0mm	3.3 x 7.0mm
PACKAGING	100m Plastic Reel (5 per box) 500m Wooden Reel (1 per box)	100m Plastic Reel (3 per box) 500m Wooden Reel (1 per box)

TDS# MSEC SPK CLR 08042016v1

Disclaimer: Although Maser Communications NZ Limited makes every reasonable effort to ensure their accuracy at the time of this publication, information and specifications described herein are subject to error or omission and to change without notice. Maser provides the information and specifications herein on an "AS IS" basis, with no representations or warranties, whether express, statutory or implied. In no event will Maser be liable for any damages (including consequential, indirect, incidental, special, punitive, or exemplary damages) whatsoever, even if Maser has been advised of the possibility of such damages, whether in an action under contract, negligence or any other theory, arising out of or in connection with the use, or inability to use, the information or specifications described herein.