

FLEXIBLE DUCTING - ComFlex

Diameter (mm)	Length (m)	Nude	Nude (Boxed)	Thermally Insulated
				R0.6 (40mm)
		Order Code	Order Code	Order Code



100	1		DCT0357	
	3	DCT0367	DCT0328	
	6	DCT0409		
125	1		DCT0358	
	3	DCT0368	DCT0329	
	6	DCT0410		
150	1		DCT0359	
	3	DCT0369	DCT0330	DCT0088
	6	DCT0411		DCT0399
200	3	DCT0377	DCT0331	DCT0089
	6	DCT0412		DCT0343
250	3	DCT0370	DCT0332	DCT0400
	6	DCT0413		DCT0344
300	3	DCT0380		DCT0401
	6	DCT0414		DCT0402
350	3	DCT0415		DCT0403
	6	DCT0416		DCT0404
400	3	DCT0417		DCT0405
	6	DCT0418		DCT0406

- DUCT CORE: Aluminium foil laminated onto polyester film
- DUCT SLEEVE: Fire retardant 75µm black low density UV-stabilised polyethylene
- TEMPERATURE RANGE: Maximum: +80°C, Minimum: -10°C
- COLOUR: Silver with black sleeve

Note

1. No glued/adhesive duct should be installed in a compressed or ovalised state for fear of long term failure
2. Products with the "order code" shown are generally ex. stock lines - other products are available to order
3. Should you have an ongoing requirement for an item that is not a standard stock line - PLEASE discuss with us and we will review stocking the item for you