



ⓘ Discontinued

Main

Range	Actassi
Product brand	Schneider Electric
Product type	30Mech modular jack
Provided equipment	Without shutter
Colour tint	White
Wiring Colour configuration	TIA-568A/B
Type of packing	Plastic bag and carton
Quantity per set	Set of 1

Complementary

[In] rated current	1.5 A at 25 °C
Voltage proof	1000 V AC/DC peak, between contacts
Contact resistance	20 mOhm
Insulation resistance	>= 500 MOhm
Connector type	RJ45
AWG gauge	AWG 24...AWG 23
Tool type	Punch down tool Quick termination tool
Cable outer diameter	0.7...1.4 mm
Compatible LAN cable types	UTP
Communication network category	6
Supported applications	1000BASE-T
Product compatibility	RJ45 plug RJ11 plug
Type of footprint	S-110 30 mech
Targeted region	Asia Pacific

Environment

Operational temperature range	-10...60 °C
Ambient air temperature for storage	-20...70 °C
Climatic category	40/070/21 (21 days)

Flame retardance	UL94-V0 conforming to UL listed
Environmental characteristic	REACH RoHS compliant
Product certifications	FCC part 68 F IEC 60603-7
Standards	IEC 11801 class E TIA/EIA 568 B NZS 3080:2003

Packing Units

Package 1 Weight	0.010 kg
Package 1 Height	0.300 dm
Package 1 width	0.300 dm
Package 1 Length	0.200 dm

Offer Sustainability

EU RoHS Directive	Compliant EU RoHS Declaration
Toxic heavy metal free	Yes
Mercury free	Yes
RoHS exemption information	Yes
China RoHS Regulation	China RoHS declaration Pro-active China RoHS declaration (out of China RoHS legal scope)
Environmental Disclosure	Product Environmental Profile

Contractual warranty

Warranty	18 months
----------	-----------