



Main

Range	PDL Iconic
Product or component type	Dimmer
Device presentation	Mechanism
Colour tint	Vivid white (VW)
Type of packing	Box
Load type	Dimmable LED - 350 W - 240 V AC Incandescent - 350 W - 240 V AC Low voltage halogen lamp with electronic transformer - 350 W - 240 V AC Dimmable fluocompact lamp - 150 W - 240 V AC Low voltage halogen lamp with iron core transformer - 350 W - 240 V AC Dimmable fluorescent - 150 W - 240 V AC

Complementary

Range compatibility	PDL Iconic
Control type	Rotary knob
Fixing mode	Clip-in
Surface finish	Glossy
Ambient air temperature for storage	0...60 °C
Dimmer control	315° rotary setting
[Ie] rated operational current	1.5 A
[Ue] rated operational voltage	220...240 V AC 50 Hz 1 W
Function available	Brightness adjustment
Protection type	Short-circuit
Ambient air temperature for operation	0...45 °C
Relative humidity	0...90 %
Connections - terminals	Flying leads
Material	PC (UL94 V-2): top PC MAS056 (UL94 V-2): bottom

Height	22.5 mm
Width	22.5 mm
Depth	39 mm
Embedding depth	37 mm

Environment

Derating factor	1 deviceswithout derating 2 deviceswith derating factor 3 deviceswith derating factor
Standards	AS/NZS 60669.2.1

Packing Units

Package 1 Weight	60 g
Package 2 Weight	446 g
Package 3 Weight	5.824 kg

Offer Sustainability

Sustainable offer status	Green Premium product
REACH Regulation	REACH Declaration
EU RoHS Directive	Compliant EU RoHS Declaration
Mercury free	Yes
RoHS exemption information	Yes
China RoHS Regulation	China RoHS declaration Product out of China RoHS scope. Substance declaration for your information
Environmental Disclosure	Product Environmental Profile
Circularity Profile	End of Life Information