

## Product data sheet

### Characteristics

# PDL387M4R

## Iconic - 4position rotary switch mechanism 10A 250V vivid white



### Main

Range of product	PDL Iconic
Product or component type	Switch
Device presentation	Mechanism
Provided equipment	Switch
Device application	Lighting
Colour	Vivid white (VW) Anthracite (AN) Cool grey (CY) Warm grey (WY)
Type of packing	Polybag
Quantity per set	Set of 20
Sale per indivisible quantity	1
Motor M-rating AS3133	M40
Load type	Inductive Motor

### Complementary

Switch function	4 positions
Control type	Rotary
Actuator	Rotary
Fixing mode	Locking bar
Marking	0 - 1 - 2 - 3
Surface finish	Matt
Surface treatment	Untreated
Rated current	10 A at 250 V AC 50 Hz
Electrical durability	20000 cycles conforming to AS/NZS 60669
Connections - terminals	4 screw terminals
Screwdriver shape	Philips No 2 Square drive no 1 (SQ1)
Clamping connection capacity	1.5 mm <sup>2</sup> for stranded cable(s) 1.5 mm <sup>2</sup> for flexible cable(s) 1.5 mm <sup>2</sup> for rigid cable(s)
Wire stripping length	10 mm
Material	PC (polycarbonate): housing PA66: housing PC (polycarbonate): knob ABS (acrylonitrile butadiene-styrene): knob cap
Height	23 mm
Width	23 mm
Depth	50 mm
Net weight	0.001 kg

The information provided in this documentation contains general descriptions and/or technical characteristics of the performance of the products contained herein. This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications. It is the duty of any such user or integrator to perform the appropriate and complete risk analysis, evaluation and testing of the products with respect to the relevant specific application or use thereof. Neither Schneider Electric Industries SAS nor any of its affiliates or subsidiaries shall be responsible or liable for misuse of the information contained herein.

## Environment

Ambient air temperature for storage	0...60 °C
Ambient air temperature for operation	0...45 °C
Relative humidity	10...95 %
Product certifications	RCM

## Offer Sustainability

Sustainable offer status	Green Premium product
REACH Regulation	<a href="#">REACH Declaration</a>
EU RoHS Directive	Compliant <a href="#">EU RoHS Declaration</a>
Mercury free	Yes
RoHS exemption information	<a href="#">Yes</a>
China RoHS Regulation	<a href="#">China RoHS Declaration</a>
Environmental Disclosure	<a href="#">Product Environmental Profile</a>