

# PVC Neutral Screened Cables

CU NSCRN 4X 6 3.2

## Contact

General Sales inquiries  
Phone: 0508 NEXANS  
sales.nz@nexans.com

Nexans ref.: [HAGP11PX004CXEM](#)

Country ref.: 3341

Cu conductors, PVC insulation, Cu wire neutral screen, Black PVC sheath. 0.6/1 kV.  
Made to AS/NZS 4961.

## DESCRIPTION

### Application

- Industrial, commercial and domestic applications
- For use in various situations to supply the main power from the point of supply to buildings, equipment, sheds, eg, switch board to main control cabinet, main between floors and buildings, cable cabinet to motor, etc.



## STANDARDS

National AS/NZS 4961

# PVC Neutral Screened Cables

CU NSCRN 4X 6 3.2

## Contact

General Sales inquiries  
Phone: 0508 NEXANS  
sales.nz@nexans.com

## CHARACTERISTICS

### Construction characteristics

Pilot wires	None
Conductor material	Copper
Type of conductor	Circular, stranded
Insulation	PVC
Screen	Copper wire
Outer sheath	PVC
With Green/Yellow core	No
With smaller neutral conductor	No
Core identification	Red, White, Blue, Black

### Dimensional characteristics

Number of cores	4
Conductor cross-section	6 mm <sup>2</sup>
Nominal overall diameter	20.6 mm
Gland Size (A2 or A2F)	32
Gland Size (CX/Z)	25
Nominal outer sheath thickness	3.2 mm
Approximate weight	0.66 kg/m

### Electrical characteristics

Max. DC resistance of the conductor at 20°C	3.08 Ohm/km
Rated Voltage U <sub>0</sub> /U (Um)	0.6/ 1 (1.2) kV

### Mechanical characteristics

Cable flexibility	Rigid
-------------------	-------

### Usage characteristics

Max. conductor temperature in service	75 °C
---------------------------------------	-------

## CORE COLOURS

No. of Cores	Colour
1	RD
1 (Plus Pilot)	RD, OG
2	RD, WH
2 (Plus Pilot)	RD, WH, OG
3	RD, WH, BU
4	RD, WH, BU, BK

# PVC Neutral Screened Cables







CU NSCRN 4X 6 3.2

## Contact







General Sales inquiries  
Phone: 0508 NEXANS  
sales.nz@nexans.com

## CURRENT CARRYING CAPACITIES THREE PHASE (IN AMPS) - THREE & FOUR CORE PVC NEUTRAL

Copper conductor Circular stranded Insulation PVC Max. Conductor Temperature 75C

Conductor cross-section [mm <sup>2</sup> ]						
	Cu	Cu	Cu	Cu	Cu	Cu
2.5	26	25	23	28	28	13
4	35	33	29	36	36	17
6	46	42	38	46	46	22
10	62	58	50	61	61	29
16	82	78	66	106	80	39

 Air Spaced from Surface, Unenclosed	 Air touching, unenclosed	 Air enclosed
 Buried direct	 Buried in single-way duct	 Cable surrounded by thermal insulation, unenclosed