

Remolex Cables

CU REMOLEX 2X 1.5+1.5E

Contact

General Sales inquiries
Phone: 0508 NEXANS
sales.nz@nexans.com

Nexans ref.: CNHQ05AA002CXHF

Country ref.: 4948

Cu Conductors, PVC insulation, Laid up, Black PVC sheath, 450/750 V. Made to AS/NZS 5000.2. Circular multicore with integral earth.

DESCRIPTION

Application

- Industrial, commercial and domestic applications
- Small mains cables.



STANDARDS

National AS/NZS 5000.2

CHARACTERISTICS

Construction characteristics

Conductor material	Copper
Type of conductor	Circular, stranded
Insulation	PVC
Outer sheath	PVC
With Green/Yellow core	Yes
With smaller neutral conductor	No
Core identification	Red, Black, Green/Yellow

Dimensional characteristics

Number of cores	3
Conductor cross-section	1.5 mm ²
Earth conductor cross section	1.5 mm ²
Nominal overall diameter	8.9 mm
Gland Size (A2 or A2F)	20S
Approximate weight	0.12 kg/m

Electrical characteristics

Rated Voltage U ₀ /U	450/750 V
Rated Voltage U ₀ /U (U _m)	450 / 750 V
Max. DC resistance of the conductor at 20°C (Ohm/km)	13.6

Mechanical characteristics

Cable flexibility	Rigid
-------------------	-------

Usage characteristics







Max. conductor temperature in service	75 °C
U.V resistance	Yes







CORE COLOURS

No. of Cores	Colour
3	RD, BK, GNYE
4	RD, WH, BU, GNYE
5	RD, WH, BU, BK, GNYE

CURRENT CARRYING CAPACITIES THREE PHASE (IN AMPS) - THREE & FOUR CORE REMOLEX PVC

Copper conductor Circular stranded Insulation PVC Max. Conductor Temperature 75C

Conductor cross-section [mm ²]						
	Cu	Cu	Cu	Cu	Cu	Cu
1.5	18	17	16	20	20	9
2.5	26	25	23	28	28	13
4	35	33	29	36	36	17
6	46	42	38	46	46	22
10	62	58	50	61	61	29
16	82	78	66	106	80	39

 Air Spaced from Surface, Unenclosed	 Air touching, unenclosed	 Air enclosed
 Buried direct	 Buried in single-way duct	 Cable surrounded by thermal insulation, unenclosed

Note

© Copyright Standards New Zealand 2012.

Content in this table and the typical New Zealand installation conditions are derived from AS/NZS 3008.1.2:2010 and has been reproduced or adapted with permission from Standards New Zealand under Copyright Licence 000926.

Please refer to the complete Standard for full details available for purchase from Standards New Zealand at www.standards.co.nz.

The values are for typical New Zealand installation conditions of:

- Ambient Air Temperature: 30°C
- Soil Temperature: 15°C
- Soil Thermal Resistivity: 1.2 K.m/W
- Depth of Burial: 0.5 m