

## ■ QUICK ASSEMBLY STRAIGHT SOCKETS SERIES 690

### MAIN TECHNICAL FEATURES:

- Straight industrial plugs according to the Standard EN 60309.
- In currents of 16, 32, 63 and 125 A.
- Protection degree IP67.
- Stainless steel springs for lid closing.
- Fast assembly without tools.
- Screw terminals.
- Resistance to chemical or atmospheric agents.

CE

IP67

## ■ Quick assembly straight sockets - EN 60309 - In 16A - IP67

ITEM	COLOUR	POLES	NOMINAL VOLTAGE	REFERENCE h	PACKAGING PIECES
EC69482*	■	2P	20-25V~	without reference	10/80
EC69483*	■	3P	20-25V~	without reference	10/60
EC69184	■	2P+⊕	100-130 V~	4	10/80
EC69185	■	3P+⊕	100-130 V~	4	10/60
EC69081	■	2P+⊕	200-250 V~	6	10/80
EC69284	■	3P+⊕	200-250 V~	9	10/60
EC69285	■	3P+N+⊕	208-250 V~	9	10/40
EC69083	■	3P+⊕	380-415 V~	6	10/60
EC69085	■	3P+N+⊕	346-415 V~	6	10/40

## ■ Quick assembly straight sockets - EN 60309 - In 32A - IP67

ITEM	COLOUR	POLES	NOMINAL VOLTAGE	REFERENCE h	PACKAGING PIECES
EC69186	■	2P+⊕	100-130 V~	4	10/60
EC69187	■	3P+⊕	100-130 V~	4	10/60
EC69286	■	2P+⊕	200-250 V~	6	10/60
EC69287	■	3P+⊕	200-250 V~	9	10/60
EC69087	■	3P+⊕	380-415 V~	6	10/40
EC69089	■	3P+N+⊕	346-415 V~	6	10/40

## ■ Quick assembly straight sockets - EN 60309 - In 63A - IP67

ITEM	COLOUR	POLES	NOMINAL VOLTAGE	REFERENCE h	PACKAGING PIECES
EC69288	■	2P+⊕	200-250 V~	6	2/16
EC69289	■	3P+⊕	200-250 V~	9	2/16
EC69380	■	3P+⊕	380-415 V~	6	2/16
EC69381	■	3P+N+⊕	346-415 V~	6	2/16

## ■ Quick assembly straight sockets - EN 60309 - In 125A - IP67

ITEM	COLOUR	POLES	NOMINAL VOLTAGE	REFERENCE h	PACKAGING PIECES
EC69681	■	2P+⊕	200-250 V~	6	2/8
EC69684	■	3P+⊕	200-250 V~	9	2/8
EC69683	■	3P+⊕	380-415 V~	6	2/8
EC69685	■	3P+N+⊕	346-415 V~	6	2/8

\* item available on request



EC69186



EC69286



EC69087